



SAE 4SH / EN856

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F) + 125°C (257°F) Intermittent
- Application** : Extra High Pressure Hydraulics
- Tube** : Oil Resistant Synthetic Rubber
- Reinforcement** : 4 High Tensile Steel Wire Spirals
- Cover** : Synthetic Rubber - Abrasion, Ozone And Weather Resistant
- Impulse Cycles** : Minimum 400,000
- Branding** : **Black Transfer Tape With White Text `SUNFLEX SAE 4SH / EN856`**

Hose Size					Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
Part Number	dash	I.D.		O.D.	psi	bar	psi	bar	inch	mm	m/kg
		inch	mm	mm							
4SHB-12	-12	3/4	19.0	32.0	6090	420	25520	1760	11.0	210	1.445
4SHB-16	-16	1	25.4	38.4	5583	385	25520	1760	13.3	220	2.015
4SHB-20	-20	1-1/4	31.8	45.2	5075	350	20300	1400	18.1	420	2.355
4SHB-24	-24	1-1/2	38.1	53.0	4350	300	18850	1300	22.0	560	3.15
4SHB-32	-32	2	50.8	67.6	3625	250	14790	1020	27.5	700	4.320