



OSD150 - (FLAT CORRUGATED) OIL SUCTION/DISCHARGE HOSE 150 PSI

Tank Truck And Tank Wagon Suction And Delivery Hose. It Withstands The Full Vacuum, Used For A Wide Range Of Petroleum Products Up To 50% Aromatic Content.

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F)
- Tube** : Black, Smooth, Nitrile Compound
- Reinforcement** : High Strength Synthetic Cord Plus Helix Wire And Anti-Static Copper Wire
- Cover** : Black, Flat Corrugated (Wrapped Finish) Special Synthetic Rubber, Compounded For An Excellent Resistance To Weather., Ozone, Abrasion And Oil. Sea Water Resistant.
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Red Transfer Tape With Negative Text
'SUNFLEX OSD 150 OIL SUCTION/DELIVERY HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
OSD150-0075-FC	19	3/4	29	1-3/16	10	150	30	450	55	0.46	0.14
OSD150-0100-FC	25	1	36	1-3/8	10	150	30	450	75	0.61	0.19
OSD150-0125-FC	32	1-1/4	43	1-21/32	10	150	30	450	90	0.85	0.26
OSD150-0150-FC	38	1-1/2	49	1-31/32	10	150	30	450	115	0.99	0.30
OSD150-0200-FC	51	2	63	2-13/32	10	150	30	450	145	1.50	0.46
OSD150-0250-FC	63	2-1/2	77	3-1/32	10	150	30	450	195	2.10	0.64
OSD150-0300-FC	76	3	90	3-5/8	10	150	30	450	240	2.58	0.79
OSD150-0400-FC	102	4	117	4-47/64	10	150	30	450	340	3.80	1.16
OSD150-0500-FC	127	5	145	5-51/64	10	150	30	450	450	6.20	1.89
OSD150-0600-FC	152	6	172	6-25/32	10	150	30	450	650	8.60	2.62
OSD150-0800-FC	203	8	225	8-15/16	10	150	30	450	900	12.43	3.79