



## OSD150 OIL SUCTION/DISCHARGE HOSE 150 PSI

Tank Truck And Tank Wagon Suction And Delivery Hose. It Withstands The Full Vacuum, Used For A Wide Range Of Petroleum Products Up To 50% Aromatic Content.

**Temperature Range** : -40°C (-40°F) to +100°C (+212°F)

**Tube** : Black, Smooth, Nitrile Compound

**Reinforcement** : High Strength Synthetic Cord Plus Helix Wire And Anti-Static Copper Wire

**Cover** : Black, Smooth (Wrapped Finish) High Grade Chloroprene Rubber, Compounded For An Excellent Resistance To Weather., Ozone, Abrasion And Oil.

**Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request

**Branding** : Red Transfer Tape With Negative Text

**'SUNFLEX OSD 150 OIL SUCTION/DELIVERY HOSE WPSI 150'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
OSD150-0075	19	3/4	30	1-3/16	10	150	30	450	75	0.59	0.40
OSD150-0100	25	1	35	1-3/8	10	150	30	450	150	0.79	0.54
OSD150-0125	32	1-1/4	42	1-21/32	10	150	30	450	192	0.97	0.66
OSD150-0150	38	1-1/2	51	1-31/32	10	150	30	450	228	1.40	0.96
OSD150-0175	45	1-3/4	57	2-15/64	10	150	30	450	266	1.43	0.98
OSD150-0200	51	2	62	2-13/32	10	150	30	450	306	1.81	1.24
OSD150-0250	63	2-1/2	77	3-1/32	10	150	30	450	378	2.28	1.56
OSD150-0300	76	3	92	3-5/8	10	150	30	450	456	2.93	2.01
OSD150-0350	90	3-1/2	104	4-3/32	10	150	30	450	540	3.46	2.37
OSD150-0400	102	4	120	4-47/64	10	150	30	450	612	4.95	3.36
OSD150-0500	127	5	147	5-51/64	10	150	30	450	762	6.60	4.43
OSD150-0600	152	6	172	6-25/32	10	150	30	450	912	7.80	5.24
OSD150-0800	203	8	227	8-15/16	10	150	30	450	1650	9.00	6.05
OSD150-1000	254	10	282	11-7/64	10	150	30	450	2035	20.03	13.46
OSD150-1200	305	12	341	13-7/16	10	150	30	450	2600	28.50	19.15