



## SAE 4SP / EN856

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F) + 125°C (257°F) Intermittent
- Application** : Extra High Pressure Hydraulics
- Tube** : Oil Resistant Synthetic Rubber
- Reinforcement** : 4 High Tensile Steel Wire Spirals
- Cover** : Synthetic Rubber - Abrasion, Ozone And Weather Resistant
- Impulse Cycles** : Minimum 400,000
- Branding** : **Black Transfer Tape With White Text `SUNFLEX SAE 4SP / EN856`**

Part Number	Hose Size				Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
	dash	I.D.		O.D.	psi	bar	psi	bar	inch	mm	kg/m
		inch	mm	mm							
R9R-04	-4	1/4	6.4	18.1	7250	500	29000	2000	5.9	150	0.600
R9R-06	-6	3/8	9.5	21.2	6450	445	25800	1780	7.1	180	0.765
R9R-08	-8	1/2	12.7	24.4	6020	415	24070	1660	9.0	230	0.910
R9R-10	-10	5/8	15.9	28.0	5510	380	23200	1600	9.8	250	1.090
R9R-12	-12	3/4	19.0	32.0	5510	380	23200	1600	11.8	300	1.545
R9R-16	-16	1	25.4	39.5	4640	320	20300	1400	13.3	340	1.970
R9R-20	-20	1-1/4	31.8	50.6	3045	210	12180	840	18.1	460	3.140
R9R-24	-24	1-1/2	38.1	57.0	2685	185	10730	740	22.0	560	3.760
R9R-32	-32	2	50.8	69.6	2395	165	9570	660	25.9	660	4.880