



SAE 4SP / EN856

Temperature Range	: -40°C (-40°F) to +100°C (+212°F) + 125°C (257°F) Intermittent
Application	: Extra High Pressure Hydraulics
Tube	: Oil Resistant Synthetic Rubber
Reinforcement	: 4 High Tensile Steel Wire Spirals
Cover	: Synthetic Rubber - Abrasion, Ozone And Weather Resistant
Impulse Cycles	: Minimum 400,000
Branding	: Positive Pink `SUNFLEX SAE 4SP / EN856`

Part Number	Hose Size				Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
	dash	I.D.		O.D.	psi	bar	psi	bar	inch	mm	m/kg
		inch	mm	mm							
R9R-06	-6	3/8	9.5	21.2	6450	445	25800	1780	7.1	180	0.765
R9R-08	-8	1/2	12.7	24.4	6020	415	24070	1660	9.0	230	0.910
R9R-10	-10	5/8	15.9	28.0	5510	380	23200	1600	9.8	250	1.090
R9R-12	-12	3/4	19.0	32.0	5510	380	23200	1600	11.8	300	1.545
R9R-16	-16	1	25.4	39.5	4640	320	20300	1400	13.3	340	1.970
R9R-20	-20	1-1/4	31.8	50.6	3045	210	12180	840	18.1	460	3.140
R9R-24	-24	1-1/2	38.1	57.0	2685	185	10730	740	22.0	560	3.760
R9R-32	-32	2	50.8	69.6	2395	165	9570	660	25.9	660	4.880