



CONTRACTOR HOSE

For Water Suction And Delivery, In Agricultural Industrial And Construction.

- Temperature Range** : -35°C (-31°F) to +70°C (+158°F)
- Tube** : Black, Natural And Synthetic Rubber
- Reinforcement** : High Tensile Synthetic Textile Fabric, Steel Wire Helix Embedded Between The Layers
- Cover** : Black, Abrasion, Weather And Ozone Resistant, Synthetic Rubber - Corrugated With Cuffed Ends (230mm)
- Branding** : Black Cover With Embossed Tape
'SUNFLEX CONTRACTOR HOSE WPSI 75'

Part Number	I.D.		O.D.		Cuff End Length	Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch		mm	bar	psi	bar		psi	mm
CONTRACTOR-0300	76.2	3	88.0	3-15/32	95	5	75	15	225	300	2.710	1.818
CONTRACTOR-0400	101.6	4	114.0	4-31/64	123	5	75	15	225	500	3.815	2.559
CONTRACTOR-0600	152.4	6	167.0	6-37/64	176	5	75	15	225	950	7.255	4.866
CONTRACTOR-0800	203.0	8	224.0	8-13/16	240	5	75	15	225	1200	12.575	8.434
CONTRACTOR-1000	254.0	10	279.0	10-63/64	294	5	75	15	225	1500	18.755	12.579