



XLPE150 CHEMICAL SUCTION/DISCHARGE HOSE 150 PSI

Madrel Built Rubber Hose Which, Thanks To Its Specially Compounded Cross-linked Polyethylene Tube, Handles A Wide Range Of Chemicals, Petroleum Products (Including Aromatics) And Oils.

- Temperature Range** : -40°C (-40°F) to +80°C (+176°F)
- Tube** : Translucent, Smooth, Cross-linked Polyethylene
- Reinforcement** : High Strength Synthetic Cord Plus Helix Wire; Anti-static Copper Wires Embedded On The Hose Body
- Cover** : Green, Smooth (Wrapped Finish) EPDM Rubber, Specially Compounded For Higher Resistance To Weather, Ozone And Abrasion
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Yellow Transfer Tape With Negative Text
'SUNFLEX XLPE 150 MULTI-PURPOSE CHEMICAL HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
XLPE150-0100	25	1	41	1-39/64	10	150	40	600	200	1.05	0.68
XLPE150-0125	32	1-1/4	48	1-57/64	10	150	40	600	256	1.35	0.91
XLPE150-0150	38	1-1/2	54	2-1/8	10	150	40	600	304	1.56	1.04
XLPE150-0200	51	2	67	2/41-64	10	150	40	600	408	2.08	1.40
XLPE150-0250	63	2-1/2	81	3-3/16	10	150	40	600	504	2.52	1.78
XLPE150-0300	76	3	95	3-13/16	10	150	40	600	608	3.61	2.39
XLPE150-0400	102	4	120	4-23/32	10	150	40	600	816	4.98	3.26

Other size, pressure ratings and colours available on request