



## AH600 AIR/WATER HOSE 600 PSI

Designed For The Most Severe Working Conditions In Mining, Quarries, Industrial And Construction Service. This Mandrel Built Hose Has A High Margin Safety And Gives A Long And Trouble-Free Service Under The Most Arduous Working Conditions.

- Temperature Range** : -40°C (+40°F) to +100°C (+212°F)
- Tube** : Black, Smooth, Synthetic Rubber, Oil Mist Resistant
- Reinforcement** : Piles Of Steel Wire Cord
- Cover** : Yellow, Smooth (Wrapped Finish) Long Lasting Synthetic Rubber, Weather And Abrasion Resistant
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Black Transfer Tape With Negative Text  
**'SUNFLEX AH600 HEAVY DUTY AIR HOSE WPSI 600'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
AH600-0050	13	1/2	24	15/16	40	600	210	3150	130	0.51	0.34
AH600-0075	19	3/4	31	1-7/32	40	600	160	2400	133	0.74	0.50
AH600-0100	25	1	38	1-11/16	40	600	160	2400	175	0.91	0.65
AH600-0125	32	1-1/4	45	1-57/64	40	600	160	2400	224	1.51	1.04
AH600-0150	38	1-1/2	56	2-7/32	40	600	160	2400	266	1.93	1.30
AH600-0200	51	2	69	2-11/16	40	600	160	2400	357	2.40	1.65
AH600-0250	63.5	2-1/2	81	3-1/8	40	600	160	2400	441	2.90	2.00
AH600-0300	76	3	95	3-7/8	40	600	160	2400	532	4.68	3.21
AH600-0400	102	4	120	5	40	600	160	2400	714	7.34	5.04
AH600-0600	152.4	6	175	6-7/8	40	600	120	1800	1215	10.30	6.98