



MSH301 MULTISERVIZ HOSE 300 PSI

Designed for general industrial applications where contact with oil/grease is frequent. Suitable for air, water and oil in separate occasions. Not suitable for chemical and abrasive medium.

Temperature Range : -20°C(-4°F) to +80°C (+176°F)

Tube : Black, smooth, synthetic rubber.

Reinforcement : High strength synthetic yarn.

Cover : Red, smooth, synthetic rubber, weathering and ozone resistant.

'SUNFLEX MSH301 PREMIUM MULTI-PURPOSE HOSE WPSI 300'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Max.Hose Length	
	mm	inch	mm	Inch	bar	psi	bar	psi	m	ft
MSH301-0025	6.4	1/4	13	33/64	20	300	60	900	100	330
MSH301-0031	7.9	5/16	15	19/32	20	300	60	900	100	330
MSH301-0038	9.5	3/8	17	2/3	20	300	60	900	100	330
MSH301-0050	12.7	1/2	21	53/64	20	300	60	900	100	330
MSH301-0063	15.9	5/8	26	1	20	300	60	900	100	330
MSH301-0075	19.1	3/4	29	1-1/7	20	300	60	900	100	330
MSH301-0100	25.4	1	36	1-11/32	20	300	60	900	100	330

page-1

