



SH250 STEAM HOSE 270 PSI

Mandrel Built High Pressure Wire Reinforced Steam Hose Designed For Service With Superheated Steam In Heat Control, Fire Prevention etc. In Many Industries At Max Pressure 18 atm (270 PSI).

- Temperature Range** : -40°C (-40°F) to +220°C (+430°F) ; intermitent to +232°C (+450°F)
- Tube** : Black, Smooth, EPDM Rubber Specially Compounded To Withstand Super Heated Steam
- Reinforcement** : Plies Of Steel Wire Cord
- Cover** : Red, Smooth (Wrapped Finish) EPDM Rubber With Excellent Resistance To High Temperature Weathering, Abrasion And Ageing. It Is Pin-Pricked to Prevent Separation.
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Red Cover With Embossed Tape
'SUNFLEX SH250 STEAM HOSE WPSI 270 TEMP 220°C INTERMITTENT TO 232°C EXCEEDS BS 5342 TYPE 2'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
SH250-0050	13	1/2	25	1	18	270	180	2700	91	0.53	0.36
SH250-0075	19	3/4	32	1-7/32	18	270	180	2700	133	0.69	0.46
SH250-0100	25	1	39	1-29/64	18	270	180	2700	175	0.9	0.62
SH250-0125	32	1-1/4	46	1-13/16	18	270	180	2700	224	1.30	0.87
SH250-0150	38	1-1/2	54	2-1/8	18	270	180	2700	266	1.60	1.10
SH250-0200	51	2	67	2-41/64	18	270	180	2700	357	2.20	1.51
SH250-0250	63	2-1/2	83	3-5/16	18	270	180	2700	445	3.80	2.61
SH250-0300	76	3	95	3-13/16	18	270	180	2700	532	4.66	3.20
SH250-0400	102	4	124	4-7/8	18	270	180	2700	714	6.50	4.46