



SH260 - HEL STEAM HOSE 260 PSI

Hardwall hose with steel cord reinforcement for steam at maximum working pressure 18 bar, used in chemical industries and industrial application in general, where a particular bending radius is necessary.

- Temperature Range** : -40°C (-40°F) to +210°C (+410°F); intermittent to +230°C (+466°F)
- Tube** : Black colour, EPDM rubber resistant to high temperature steam
- Reinforcement** : Double steel wire braids with helical wire
- Cover** : Red Colour, EPDM rubber resistant to heat and weather.
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Red Cover With Embossed Tape

**‘SUNFLEX SH260-HEL STEAM HOSE WPSI 260 TEMP 210°C INTERMITTENT TO 230°C
EN ISO 6134:2017 - TYPE 2’**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
SH260-0200-HEL	51	2	69	2-5/7	18	260	180	2610	700	2.971	2.996
SH260-0250-HEL	63	2-1/2	86	3-2/5	18	260	180	2610	850	4.574	3.076
SH260-0300-HEL	76	3	98	3-6/7	18	260	180	2610	980	5.335	3.585