



SH260 STEAM HOSE 260 PSI

High temperature steam Lines at constant pressure of 290 PSI

Applicable Standard: Exceeds IS 10655 TYPE 3/ ISO 6134 TYPE 2A/ BS 5342 TYPE 2A

Temperature Range : -40°C (-40°F) to +210°C (+410°F); intermittent to +230°C (+466°F)

Tube : Black colour, EPDM rubber resistant to high temperature steam

Reinforcement : Double steel wire braids

Cover : Red Colour, EPDM rubber resistant to heat and weather.

Coils : 61mt (200ft) Continuous Length; Other Length Available On Request

Branding : Red Cover With Embossed Tape

**'SUNFLEX SH260 STEAM HOSE WPSI 260 TEMP 210°C INTERMITTENT TO 230°C
EN ISO 6134:2017 - TYPE 2'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
SH260-0038	10	3/8	19.5	7/9	18	260	180	2610	130	0.421	0.283
SH260-0050	12.5	1/2	23	1	18	260	180	2610	150	0.589	0.396
SH260-0075	19	3/4	30	1-1/6	18	260	180	2610	230	0.846	0.568
SH260-0100	25.4	1	36.8	1-4/9	18	260	180	2610	300	1.095	0.736
SH260-0125	32	1-1/4	43.5	1-5/7	18	260	180	2610	375	1.505	1.011
SH260-0150	38	1-1/2	49.5	2	18	260	180	2610	455	1.780	1.196
SH260-0200	51	2	64	2-1/2	18	260	180	2610	600	2.261	1.519
SH260-0250	63	2-1/2	83	3-1/4	18	260	180	2610	675	4.214	2.832
SH260-0300	76	3	98	3-6/7	18	260	180	2610	725	4.962	3.334