



## 2K SUPER-COMPACT

- TEMPERATUR RANGE** : -40°C (-40°F) to +100°C (+212°F)
- APPLICATION** : For High Pressure Hydraulic Systems Using Hydraulic Oils, Mineral And Vegetable Lubricants
- TUBE** : Mineral, Vegetable And Hydraulic Oil Resistant Special Synthetic Rubber
- REINFORCEMENT** : 2 High Tensile Steel Wire Braid
- COVER** : Oil, Abrasion And Weather Resistant Special Synthetic Rubber
- BRANDING** : Positive White

**'SUNFLEX 2K EXCEEDS EN857 2SC'**

| Hose Size   |      |      |      |      | Max Working Pressure |     | Minimum Burst Pressure |      | Minimum Bend Radius | Hose Weight |
|-------------|------|------|------|------|----------------------|-----|------------------------|------|---------------------|-------------|
| Part Number | Dash | I.D. |      | O.D. |                      |     |                        |      |                     |             |
|             |      | inch | mm   | mm   | psi                  | bar | psi                    | bar  | mm                  | m/kg        |
| 2K-04-SF-S  | -04  | 1/4  | 6.4  | 13.4 | 6525                 | 450 | 26100                  | 1800 | 45                  | 0.300       |
| 2K-05-SF-S  | -05  | 5/16 | 8.0  | 15.0 | 6090                 | 420 | 24360                  | 1680 | 60                  | 0.345       |
| 2K-06-SF-S  | -06  | 3/8  | 9.5  | 17.4 | 5583                 | 385 | 22330                  | 1540 | 70                  | 0.460       |
| 2K-08-SF-S  | -08  | 1/2  | 12.7 | 20.6 | 5003                 | 345 | 20010                  | 1380 | 90                  | 0.585       |
| 2K-10-SF-S  | -10  | 5/8  | 16.0 | 23.7 | 4205                 | 290 | 16820                  | 1160 | 130                 | 0.675       |
| 2K-12-SF-S  | -12  | 3/4  | 19.0 | 27.7 | 4060                 | 280 | 16240                  | 1120 | 160                 | 0.855       |
| 2K-16-SF-S  | -16  | 1    | 25.4 | 35.6 | 2900                 | 200 | 11600                  | 800  | 210                 | 1.230       |