



2K SUPER-COMPACT

- TEMPERATUR RANGE** : -40°C (-40°F) to +100°C (+212°F)
- APPLICATION** : For High Pressure Hydraulic Systems Using Hydraulic Oils, Mineral And Vegetable Lubricants
- TUBE** : Mineral, Vegetable And Hydraulic Oil Resistant Special Synthetic Rubber
- REINFORCEMENT** : 2 High Tensile Steel Wire Braid
- COVER** : Oil, Abrasion And Weather Resistant Special Synthetic Rubber
- BRANDING** : Positive White

'SUNFLEX 2K EXCEEDS EN857 2SC'

Hose Size					Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius	Hose Weight
Part Number	Dash	I.D.		O.D.						
		inch	mm	mm	psi	bar	psi	bar	mm	kgs/m
2K-04-SF-S	-04	1/4	6.4	13.4	6525	450	26100	1800	75	0.29
2K-05-SF-S	-05	5/16	8.0	15.0	6090	420	24360	1680	85	0.33
2K-06-SF-S	-06	3/8	9.5	17.0	5583	385	22330	1540	90	0.42
2K-08-SF-S	-08	1/2	12.7	20.7	5003	345	20010	1380	130	0.55
2K-10-SF-S	-10	5/8	16.0	23.6	4205	290	16820	1160	150	0.65
2K-12-SF-S	-12	3/4	19.0	27.7	4060	280	16240	1120	180	0.79
2K-16-SF-S	-16	1	25.4	35.6	2900	200	11600	800	230	1.18