



## JH1232 SUNFLEX JETTING HOSE 1232 PSI

- Application** : Flexible Connection Between Main Deck And Legs Of Jack Up Rigs For Water Jetting. Abrasion Resistant Tube, Designed For High Kink Resistance.
- Temperature Range** : -30 degC to +100 degC
- Tube** : Synthetic And Natural Elastomers, Black, Smooth Antistatic, Abrasion Resistant.
- Reinforcement** : Multiple Piles Of Steel Cable
- Cover** : Synthetic And Natural Elastomers, Black, Smooth With Cloth Impression, Antistatic, Abrasion, Weather And Ozone Resistant.
- Branding** : Blue Transfer Tape With Negative Text  
'SUNFLEX JH1232 JETTING HOSE W.P.S.I 1232 '

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
JH1232-0200	50.8	2	70	2-3/4	85	1232	200	2900	508	3.41	2.36
JH1232-0250	63.5	2-1/2	88	3-15/32	85	1232	200	2900	635	4.97	3.43
JH1232-0300	76.2	3	102	4-1/64	85	1232	200	2900	762	6.58	4.54
JH1232-0400	101.6	4	130	5-1/8	85	1232	200	2900	1016	9.38	6.48
JH1232-0500	127.0	5	155	6-7/64	85	1232	200	2900	1270	10.95	7.56
JH1232-0600	152.4	6	184	7-1/4	85	1232	175	2538	1524	13.49	9.32