

BAUER QUICK COUPLING

Advantages:-

Fast: A Complete System Quickly Installed, Even In The Dark. No Tools - No Loose Parts

Flexibility: With Up To 30° Articulation On Coupling Joint. Suction And Pressure Proof, Providing Excellent Flexibility Of Installation, Ideal For Difficult Site Conditions

Strong And Durable: Produced From High-Grade High-Tensile Steel, Abrasion Resistant Hot-Dip Galvanisation According To DIN 50976 - Also Stainless Steel Option

Safe: Suction And Pressure-Proof Up To 20 Bar With All Types Of Media, Subject To Suitable Seal Material Options



Heat resistance: Resists Up To 110°C With Special Seals

Tensile Resistance: Suction And Pressure-Proof While Subject To Tensile Stress

Versatile: Suitable For Handling All Types Of Product; Hot Dip Galvanised Or Stainless Steel Product Range

Special coatings on application

Security: With Special Locking Pin System Option

		<u>Diameter (mm)</u>
	GALVANIZED FEMALE COUPLING WITH HOSE TAIL AND RUBBER GASKET	50 x 50
		76 x 63
		76 x 76
		89 x 76
		89 x 89
	GALVANIZED MALE COUPLING WITH HOSE TAIL AND LEVER RING	108 x 100
		108 x 108
		133 x 125
		159 x 150
		159 x 159
		194 x 200