



SAE 100 R15 / EN 856

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F) + 121°C (250°F) Intermittent
- Application** : Extremely High Pressure, Heavy Duty, High Impulse Hydraulics
- Tube** : Oil Resistant Synthetic Rubber
- Reinforcement** : 4 or 6 High Tensile Steel Wire Spirals
- Cover** : Synthetic Rubber - Abrasion, Ozone And Weather Resistant
- Impulse Cycles** : Minimum 500,000
- Branding** : **Positive White `SUNFLEX SAE 100 R15 / EN 856'**

Part Number	Dash	Hose Size			Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
		I.D.		O.D.	psi	bar	psi	bar	inch	mm	m/kg
		inch	mm	mm							
R15B-12	-12	3/4	19.0	32.0	6,300	420	25,200	1,680	10.5	267	1.545
R15B-16	-16	1	25.4	38.5	6,300	420	25,200	1,680	13.0	330	2.145
R15B-20	-20	1-1/4	31.8	49.6	6,300	420	25,200	1,680	17.5	445	3.975
R15B-24	-24	1-1/2	38.1	57.1	6,300	420	25,200	1,680	21.0	533	4.985
R15B-32	-32	2	51.4	71.7	6,300	420	25,200	1,680	24.8	630	6.700