



## SUNFLEX THERMOPLASTIC HOSE HOSE TYPE 714 - 1 WIRE AIRLESS PAINT SPRAY

### Sunflex Thermoplastic Hose 714 - 1 Wire Paint Spray Hose

A high pressure, high performance, airless paint spray hose specially designed to meet the exacting requirements of the industry. Steel braid reinforcing ensures strength and guaranteed electrical conductivity.

This hose offers optimum resistance to a wide range of fluids including paints, chlorinated solvents and other chemicals. Cover pin-pricked as standard.

**Applications:** Airless Paint Spray Equipment

**Construction:** Type 714 comprises of a nylon 6 tube reinforced with one braid of brass coated high tensile steel wire. The blue outer cover is polyurethane, other colours are available to special order.

**Performance:**

- Min/Max continuous service temperature range -40°C to 95°C.
- Resistant to most chemicals, paints and solvents.
- Excellent flexibility with small bend radius.
- Superior and reliable electrical conductivity resistance in the order of 1.0 ohms/metre.
- Cover provides excellent abrasion resistance.

PART NO	NOMINAL INSIDE DIAMETER		NOMINAL OUTSIDE DIAMETER		WORKING PRESSURE		BURSTING PRESSURE		MIN BEND RADIUS		WEIGHT	
	INCH	MM	INCH	MM	PSI	BAR	PSI	BAR	INCH	MM	LB/FT	KG/M
714-03-SF-PP	3/16	4.7	0.365	9.3	8120	560	20300	1400	3.0	75	0.08	0.12
714-04-SF-PP	1/4	6.4	0.460	11.7	7540	520	18850	1300	4.0	100	0.11	0.16
714-06-SF-PP	3/8	9.6	0.610	15.5	5800	400	14500	1000	5.0	127	0.15	0.23
714-08-SF-PP	1/2	12.7	0.725	18.4	2750	190	11000	758	4.5	114	0.20	0.30
714-12-SF-PP	3/4	19.0	1.020	26.0	1750	120	7000	483	8.0	200	0.29	0.43