



SUNFLEX TEST HOSE

- Temperature Range** : -40°C to +100°C (Not To Exceed +70°C For Air And Water Based Fluids)
- Application** : Very High Pressure Mini Hydraulic Lines Up To 630 Bar. Suitable For Hydraulic Application With Increased Resistance To Abrasion For Use With Petroleum, Synthetic Or Water Based Fluids In Hydraulic Systems Pressure Test Equipments And Test Points, General Mini Hydraulic Equipments. Automotive Roof And Boot Opening System And Truck's Cab Lifting Systems.
- Core** : Thermoplastic Elastomer
- Reinforcement** : Single Braid Of Aramid Fiber
- Cover** : Black Color, Polyurethane And Pin Prick Upon Request. Available With Polyamide 12 As Core And Cover.
- Branding** : Ink Jet With White Text 'SUNFLEX TEST HOSE'

Part Number	Hose Size			Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius	
	I.D.		O.D.	psi	bar	psi	bar	inch	mm
	inch	mm	mm						
TEST-02	5/64	2.0	5.0	9100	630	27300	1890	0.8	20
TEST-03	1/8	3.0	6.0	9100	630	27300	1890	1.2	30
TEST-04	5/32	4.0	8.0	9100	630	27300	1890	1.6	40