



## DH300 HEAVY DUTY OIL SUCTION & DISCHARGE DOCK HOSE

Sunflex D300 Is Designed For Loading And Unloading Of Petroleum Based Products Of Up to 50% Aromatic Content. Suitable For Bunkering Services Between Docks And Ships Under All Types Of Service Condition.

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F)  
**Tube** : Black, Oil Resistance Nitrile Rubber, Smooth Bore  
**Reinforcement** : High Tensile Synthetic Cord Incorporating Wire Helix  
**Cover** : Black, Oil , Abrasion, Ozone And Weather Resistance Chloroprene Rubber With Orange Longitudinal Stripe  
**Pressure Rating** : Working Pressure - 300 PSI / Test Pressure - 450 PSI  
**Safety Factor** : Minimum 4:1  
**Marking** : SUNFLEX DH300 SUNFLEX BUNKERING HOSE WP300PSI TP450PSI BS1435-S 15 EN1765:2004 S-15  
**Hose Assemblies Fully Conform to : BS 1435 1987 Type S15 / EN1765:2004S-15**

Part Number	Nominal Bore			Bending Radius	Swaged Fittings Weight	Hose Weight
	I.D.		O.D.			
	inch	mm	mm			
DH300-0400	4	102	126	850	9.2	6.35
DH300-0600	6	152	182	1000	17.4	11.13
DH300-0800	8	203	237	1500	28.4	16.32
DH300-1000	10	254	289	2000	42.0	21.64
DH300-1200	12	305	347	2500	46.0	30.94