



## SUNFLEX SINGLE LINE WELDING HOSE - ACETYLENE

### Comply to EN 559

For Use With Welding And Allied Processes In Workshops, Shipyards, Construction Sites And Manufacturing Industries.

<b>Operating Temperature</b>	: -25°C To +75°C
<b>Tube</b>	: High Ignition Temperature Synthetic Rubber
<b>Reinforcement</b>	: High Tensile Synthetic Textile Filament Yarn
<b>Cover</b>	: Excellent Ozone And Weather Resistant Synthetic Rubber
<b>Color</b>	: RED
<b>Surface</b>	: Ribbed
<b>Coils</b>	: 100mt Continuous Length
<b>Branding</b>	: Inkjet Black
	<b>'SUNFLEX WELDING HOSE - EN559 W/P 20 BAR B/P 60 BAR'</b>

Part Number	Nominal I.D.		O.D.	Working Pressure		Bursting Pressure	
	inch	mm	mm	psi	bar	psi	bar
WH-ACETYLENE-0019-RD	3/16	5.0	12.0	300	20	900	60
WH-ACETYLENE-0025-RD	1/4	6.0	13.0				
WH-ACETYLENE-0031-RD	5/16	8.0	15.0				
WH-ACETYLENE-0038-RD	3/8	10.0	17.0	250	17	750	50
WH-ACETYLENE-0050-RD	1/2	13.0	20.0				
WH-ACETYLENE-0063-RD	5/8	16.0	25.0				
WH-ACETYLENE-0075-RD	3/4	19.0	29.0				