



## AHT150 ASPHALT HOSE 150 PSI

A Strong Yet Flexible Hose, Specially Designed As Tank Truck Or Tank Wagon Hose For Loading And Unloading Hot Asphalt.

- Temperature Range** : -15°C (-5°F) to +185°C (+365°F)
- Tube** : Black, Smooth, Polyacrylic Compound
- Reinforcement** : Plies Of Steel Wire Cord Plus Helix Wire
- Cover** : Black, Smooth (Wrapped Finish) Special Synthetic Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion, Tar And Oil
- Coils** : Size 3/4" to 5" Supply In 61mt (200ft) Continuous Length
- Branding** : White Transfer Tape With Negative Text  
**'SUNFLEX AHT 150 ASPHALT HOSE WPSI 150'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
AHT150-0150	38.0	1-1/2	56	2-13/64	10	150	30	450	228	1.87	1.26
AHT150-0200	50.8	2	71	2-51/64	10	150	30	450	305	2.85	1.92
AHT150-0250	63.5	2-1/2	81	3-3/16	10	150	30	450	381	3.19	2.14
AHT150-0300	76.2	3	94	3-45/64	10	150	30	450	457	4.20	2.82
AHT150-0350	90.0	3-1/2	112	4-13/32	10	150	30	450	540	5.12	3.44
AHT150-0400	101.6	4	126	4-31/32	10	150	30	450	610	6.30	4.23
AHT150-0500	127.0	5	155	6-7/64	10	150	30	450	762	8.33	5.60
AHT150-0600	152.4	6	184	7-1/4	10	150	30	450	914	10.45	7.02