



## AHT220 ASPHALT HOSE 200 PSI

A Strong Yet Flexible Hose, Specially Designed As Tank Truck Or Tank Wagon Hose For Loading And Unloading Hot Asphalt.

- Temperature Range** : -15°C (-5°F) to +185°C (+365°F)
- Tube** : Black, Smooth, Polyacrylic Compound
- Reinforcement** : Plies Of Steel Wire Cord Plus Helix Wire
- Cover** : Black, Smooth (Wrapped Finish) Special Synthetic Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion, Tar And Oil
- Coils** : Size 3/4" to 5" Supply In 61mt (200ft) Continuous Length
- Branding** : White Transfer Tape With Negative Text  
**'SUNFLEX AHT 220 ASPHALT HOSE WPSI 220'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
AHT220-0150	38.0	1-1/2	56	2-13/64	15	220	45	660	228	1.87	1.26
AHT220-0200	50.8	2	71	2-51/64	15	220	45	660	305	2.83	1.90
AHT220-0250	63.5	2-1/2	81	3-3/16	15	220	45	660	381	3.00	2.01
AHT220-0300	76.2	3	94	3-45/64	15	220	45	660	457	3.56	2.40
AHT220-0350	90.0	3-1/2	112	4-13/32	15	220	45	660	540	5.05	3.40
AHT220-0400	101.6	4	126	4-31/32	15	220	45	660	610	6.19	4.16
AHT220-0500	127.0	5	155	6-7/64	15	220	45	660	762	9.02	6.06
AHT220-0600	152.4	6	184	7-1/4	15	220	45	660	914	12.43	8.35