



CFD75 CEMENT FLAT DISCHARGE HOSE

For Discharge Of Dry Cement From Tank Truck, In-plant Service And Abrasive Powders For Lorries And Silos.

- Temperature Range** : -40°C to +70°C
- Tube** : Abrasion Resistant, Antistatic Natural Rubber
- Reinforcement** : High Tensile Synthetic Textile
- Cover** : Abrasion , Ozone And Weather Resistant Natural And Synthetic Rubber
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Pink Transfer Tape With Negative Text
'SUNFLEX CEMENT FLAT DISCHARGE HOSE B.P.S.I 225 ISO 1307 '

Part Number	Size	I.D.	O.D.	Working Pressure		Bursting Pressure		Hose Weight
	inch	mm	mm	bar	psi	bar	psi	kg/m
CFD75-0200	2	50.8	60.4	5	75	15	225	0.96
CFD75-0250	2-1/2	63.5	73.0	5	75	15	225	1.18
CFD75-0300	3	76.2	86.0	5	75	15	225	1.39
CFD75-0350	3-1/2	90.0	100.0	5	75	15	225	1.77
CFD75-0400	4	101.6	112.0	5	75	15	225	2.03
CFD75-0431	4-5/16	110.0	120.0	5	75	15	225	2.10
CFD75-0500	5	127.0	137.0	5	75	15	225	2.41
CFD75-0600	6	152.4	164.0	5	75	15	225	3.41
CFD75-0800	8	203.2	215.0	5	75	15	225	4.66