



## CPH1232 - 85 BAR STEEL CONCRETE PUMPING HOSE 1232 PSI

Used For Placement Of Concrete To The Casting Locations.

- Temperature Range** : -40°C (-40°F) to +70°C (+158°F)  
**Tube** : Abrasion Resistant, Special Conductive Natural And CBR Rubber  
**Reinforcement** : High Tensile Steel Cords  
**Cover** : Abrasion, Ozone And Weather Resistant Pin-pricked Special Synthetic Rubber  
**Branding** : Yellow Transfer Tape With Negative Text  
**'SUNFLEX CPH1232 CONCRETE PUMP HOSE WPSI 1232 '**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
CPH1232-0200	50.8	2	70.0	2-3/4	85	1232	200	2900	508	3.41	2.36
CPH1232-0250	63.5	2-1/2	88.0	3-15/32	85	1232	200	2900	635	4.97	3.43
CPH1232-0300	76.2	3	102.0	4-1/64	85	1232	200	2900	762	6.58	4.54
CPH1232-0400	101.6	4	130.0	5-1/8	85	1232	200	2900	1016	9.38	6.48
CPH1232-0500	127.0	5	155.0	6-7/64	85	1232	200	2900	1270	10.95	7.56
CPH1232-0600	152.4	6	184.0	7-1/4	85	1232	175	2538	1524	13.49	9.32