



CTH150 CEMENT TANKER HOSE (CORRUGATED)

For Suction And Discharge Of Dry Bulk Materials, Sand, Gravel, Dry Cement etc.

- Temperature Range** : -40°C (-40°F) to +70°C (+158°F°)
Tube : Abrasion Resistant, Conductive Natural Rubber
Reinforcement : High Tensile Synthetic Textile, Steel Wire Helix And Antistatic Copper Wire
Cover : Abrasion, Ozone And Weather Resistant Corrugated Special Synthetic Rubber
Branding : Black Cover With Embossed Tape
'SUNFLEX CTH150 CEMENT TANKER HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
CTH150-0100	25.4	1	37.5	1-31/64	10	150	30	450	101.6	0.81	0.54
CTH150-0125	32.0	1-1/4	44.0	1-47/64	10	150	30	450	128	0.98	0.66
CTH150-0150	38.0	1-1/2	51.0	2	10	150	30	450	152	1.31	0.88
CTH150-0200	50.8	2	64.5	2-17/32	10	150	30	450	203.2	1.78	1.20
CTH150-0250	63.5	2-1/2	77.5	3-1/16	10	150	30	450	254	2.38	1.60
CTH150-0300	76.2	3	90.5	3-9/16	10	150	30	450	304	3.04	2.04
CTH150-0350	90.0	3-1/2	106.0	4-11/64	10	150	30	450	360	3.90	2.62
CTH150-0400	101.6	4	119.0	4-11/16	10	150	30	450	457	4.66	3.13
CTH150-0500	127.0	5	147.0	5-25/32	10	150	30	450	635	6.82	4.58
CTH150-0600	152.4	6	173.0	6-13/16	10	150	30	450	760	8.81	5.92
CTH150-0800	203.2	8	227.0	8-15/16	10	150	30	450	1219.2	14.07	9.45
CTH150-1000	254.0	10	279.0	10-63/64	10	150	30	450	1524	16.99	11.42