



SUNFLEX SINGLE LINE WELDING HOSE - OXYGEN

Comply to EN 559

For Use With Welding And Allied Processes In Workshops, Shipyards, Construction Sites And Manufacturing Industries.

Operating Temperature	: -25°C To +75°C
Tube	: High Ignition Temperature Synthetic Rubber
Reinforcement	: High Tensile Synthetic Textile Filament Yarn
Cover	: Excellent Ozone And Weather Resistant Synthetic Rubber
Color	: BLUE
Surface	: Ribbed
Coils	: 100mt Continuous Length
Branding	: Inkjet Black
	'SUNFLEX WELDING HOSE - EN559 W/P 20 BAR B/P 60 BAR'

Part Number	Nominal I.D.		O.D.	Working Pressure		Bursting Pressure	
	inch	mm	mm	psi	bar	psi	bar
WH-OXYGEN-0019-BE	3/16	5.0	12.0	300	20	900	60
WH-OXYGEN-0025-BE	1/4	6.0	13.0				
WH-OXYGEN-0031-BE	5/16	8.0	15.0				
WH-OXYGEN-0038-BE	3/8	10.0	17.0				
WH-OXYGEN-0050-BE	1/2	13.0	20.0	250	17	750	50
WH-OXYGEN-0063-BE	5/8	16.0	25.0				
WH-OXYGEN-0075-BE	3/4	19.0	29.0				