



WSD150 WATER SUCTION/DISCHARGE HOSE 150 PSI

Mandrel Built Heavy Water Suction & Discharge Hose, It Handles Sewage. Waste Water, Mud etc.

- Temperature Range** : -40°C (-40°F) to +85°C (+185°F)
Tube : Black, Smooth, Synthetic Rubber Resistant To Water With pH Value 5 To 8
Reinforcement : High Strength Synthetic Cord Plus Helix Wire
Cover : Black, Smooth (Wrapped Finish) Synthetic Rubber, Abrasion And Weathering Resistant
Coils : 61mt (200ft) Continuous Length; Other Length Available On Request
Branding : Yellow Transfer Tape With Negative Text
'SUNFLEX WSD 150 WATER SUCTION/DELIVERY HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
WSD150-0125	32	1-1/4	43	1-21/32	10	150	30	450	256	0.97	0.67
WSD150-0150	38	1-1/2	50	1-15/16	10	150	30	450	304	1.27	0.87
WSD150-0200	51	2	63	2-15/32	10	150	30	450	408	1.72	1.18
WSD150-0250	63	2-1/2	77	3-1/32	10	150	30	450	508	2.37	1.63
WSD150-0300	76	3	89	3-1/2	10	150	30	450	608	2.79	1.91
WSD150-0338	86	3-3/8	99	3-29/32	10	150	30	450	456	3.80	2.60
WSD150-0350	90	3-1/2	103	4-1/32	10	150	30	450	540	3.86	2.65
WSD150-0400	102	4	118	4-9/16	10	150	30	450	816	4.33	2.98
WSD150-0450	115	4-1/2	132	5-13/64	10	150	30	450	910	5.20	3.58
WSD150-0500	127	5	144	5-5/8	10	150	30	450	1010	7.23	4.97
WSD150-0600	152	6	171	6-3/4	10	150	30	450	1216	10.18	7.00
WSD150-0800	203	8	227	8-15/16	10	150	30	450	1624	14.80	9.94
WSD150-1000	254	10	280	11-1/8	10	150	30	450	2035	16.34	10.98
WSD150-1200	305	12	336	13-15/64	10	150	30	450	2600	24.63	16.55