



## CDH150 CEMENT DELIVERY HOSE 150 PSI

Bulk Materials Handling Hose, Used To Convey Cement, Sand Gravel, Silica And Other Abrasive Materials. It Is Manufactured With Anti-Static Rubber, Granting A Complete Discharge Of Static Electricity.

- Temperature Range** : -40°C (-40°F) to +85°C (+185°F)
- Tube** : Black, Smooth , Compounded For Long Wear Resistance In Handling Hard, Sharp, Abrasive Material; It Is Anti-Static
- Reinforcement** : High Strength Synthetic Cord
- Cover** : Black, Smooth (Wrapped Finish) Abrasion And Resistant Synthetic Rubber; It Is Anti-static
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Green Transfer Tape With Negative Text  
**'SUNFLEX CDH 150 BULK MATERIAL DELIVERY HOSE WPSI 150'**

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
CDH150-0300	76	3	95	3-47/64	10	150	30	450	760	3.45	2.36
CDH150-0400	102	4	122	4-13/16	10	150	30	450	1020	4.56	3.12
CDH150-0500	127	5	149	5-7/8	10	150	30	450	1270	6.01	4.12