



OROFLEX 10

Color : Black
Composition : Synthetic Rubber And Polyester-Polyamide Textile
Surface : Ribbed For Maximum Abrasion Resistance
Service : -20°baC to +80°baC
Standard Length : 30 - 60m (Up To 200m To Order)

Part Number	I.D.		Wall Thickness		Working Pressure		Burst Pressure		Tensil Strength	Bend Radius	Hose Weight
	mm	inch	mm	inch	bar	psi	bar	psi	kg	m	kg/m
OF10-0125	30	1-1/4	1.9	0.07	28	406	85	1233	2.250	0.50	0.260
OF10-0150	38	1-1/2	1.9	0.07	14	203	42	609	2.950	0.70	0.300
OF10-0175	45	1-3/4	1.9	0.07	14	203	42	609	2.350	0.90	0.350
OF10-0200	52	2	1.9	0.07	14	203	42	609	3.750	1.10	0.400
OF10-0225	60	2-1/4	2.3	0.09	14	203	42	609	5.000	1.20	0.500
OF10-0250	65	2-1/2	2.3	0.09	14	203	42	609	5.100	1.30	0.570
OF10-0275	70	2-3/4	2.3	0.09	14	203	35	508	5.200	1.35	0.580
OF10-0300	75	3	2.3	0.09	12	174	32	464	5.300	1.45	0.680
OF10-0325	80	3-1/4	2.3	0.09	12	174	32	464	5.900	1.46	0.700
OF10-0350	90	3-1/2	2.3	0.09	16	232	40	580	8.400	1.48	0.830
OF10-0400	102	4	2.3	0.09	12	174	30	435	7.900	1.70	0.930
OF10-0431	110	4-1/4	2.5	0.10	12	174	30	435	8.900	1.80	1.100
OF10-0500	127	5	2.7	0.10	12	174	30	435	9.400	2.10	1.400
OF10-0600	152	6	2.7	0.10	12	174	30	435	16.350	2.25	1.600
OF10-0800	203	8	3.4	0.13	10	150	25	363	23.600	3.00	1.848
OF10-1000	254	10	3.8	0.15	10	150	24	348	47.250	3.20	2.621



- ◆ Industrial Washdown
- ◆ Rink Flooding
- ◆ Flexible Pipeline
- ◆ Irrigation Supply
- ◆ Water Bypass Systems
- ◆ Submersible And Portable Pump Discharge
- ◆ Cable Cover
- ◆ Light Weight Sludge Supply
- ◆ Chemical Solution Transfer