



## OROFLEX 10

|                        |  |
|------------------------|--|
| <b>Color</b>           | : Black  |
| <b>Composition</b>     | : Synthetic Rubber And Polyester-Polyamide Textile |
| <b>Surface</b>         | : Ribbed For Maximum Abrasion Resistance           |
| <b>Service</b>         | : -20°baC to +80°baC                               |
| <b>Standard Length</b> | : 30 - 60m (Up To 200m To Order)                   |

| Part Number | I.D. |       | Wall Thickness | Service / Burst Pressure | Tensile Strength | Radius Of Curvature | Hose Weight |
|-------------|------|-------|----------------|--------------------------|------------------|---------------------|-------------|
|             | mm   | inch  |                |                          |                  |                     |             |
| OF10-0125   | 30   | 1-1/4 | 2              | 10/30                    | 700              | 0.500               | 0.27        |
| OF10-0150   | 38   | 1-1/2 | 2              | 10/30                    | 900              | 0.700               | 0.31        |
| OF10-0175   | 45   | 1-3/4 | 2              | 10/30                    | 1.200            | 0.900               | 0.37        |
| OF10-0200   | 52   | 2     | 2              | 10/30                    | 1.300            | 1.100               | 0.45        |
| OF10-0225   | 60   | 2-1/4 | 2              | 10/30                    | 1.400            | 1.200               | 0.50        |
| OF10-0250   | 65   | 2-1/2 | 2              | 10/30                    | 1.400            | 1.300               | 0.62        |
| OF10-0275   | 70   | 2-3/4 | 2.5            | 10/30                    | 1.700            | 1.350               | 0.65        |
| OF10-0300   | 76   | 3     | 2.5            | 10/30                    | 1.800            | 1.450               | 0.68        |
| OF10-0325   | 80   | 3-1/4 | 2.5            | 10/30                    | 1.850            | 1.450               | 0.70        |
| OF10-0350   | 90   | 3-1/2 | 2.5            | 10/30                    | 2.100            | 1.480               | 0.83        |
| OF10-0400   | 102  | 4     | 2.5            | 10/30                    | 2.400            | 1.700               | 0.95        |
| OF10-0431   | 110  | -     | 3              | 10/30                    | 4.000            | 1.800               | 1.10        |
| OF10-0450   | 115  | 4-1/2 | 3              | 10/30                    | 4.100            | 1.900               | 1.20        |
| OF10-0500   | 127  | 5     | 3              | 10/30                    | 4.200            | 2.100               | 1.45        |
| OF10-0600   | 152  | 6     | 3              | 10/30                    | 5.000            | 2.250               | 1.65        |
| OF10-0800   | 204  | 8     | 3              | 10/30                    | 6.600            | 3.000               | 2.25        |
| OF10-1000   | 254  | 10    | 3.5            | 8/24                     | 8.800            | 3.300               | 2.80        |
| OF10-1200   | 306  | 12    | 4              | 8/24                     | 10.200           | 3.600               | 3.25        |



- ◆ Industrial Washdown
- ◆ Rink Flooding
- ◆ Flexible Pipeline
- ◆ Irrigation Supply
- ◆ Water Bypass Systems
- ◆ Submersible And Portable Pump Discharge
- ◆ Cable Cover
- ◆ Light Weight Sludge Supply
- ◆ Chemical Solution Transfer