



OROFLEX 20

Color	: Yellow
Composition	: Synthetic Rubber And Polyester-Polyamide Textile
Surface	: Fine Ribbed, Highly Resistant To Abrasion
Service	: > From -20°C to +80°C
Standard Length	: 60m (Up To 200m To Order)

Part Number	I.D.		Wall Thickness		Working Pressure		Burst Pressure		Tensil Strength	Bend Radius	Hose Weight
	mm	inch	mm	inch	bar	psi	bar	psi	kg	m	kg/m
OF20-0075	20	3/4	2.0	0.08	33	483	100	1450	1.500	0.65	0.195
OF20-0100	26	1	2.0	0.08	38	556	115	1668	1.875	0.90	0.25
OF20-0150	38	1-1/2	2.8	0.11	21	305	63	914	3.000	1.10	0.45
OF20-0175	45	1-3/4	3.0	0.12	21	305	63	914	3.500	1.28	0.55
OF20-0200	52	2	3.0	0.12	21	302	52	754	3.750	1.30	0.64
OF20-0250	65	2-1/2	3.0	0.12	21	302	52	754	6.000	1.35	0.70
OF20-0300	76	3	3.0	0.12	18	261	45	653	8.500	1.45	0.90
OF20-0400	102	4	3.1	0.12	21	302	52	754	13.000	1.80	1.25
OF20-0500	127	5	3.2	0.13	17	244	42	609	15.500	1.90	1.70
OF20-0600	152	6	4.0	0.16	20	290	50	725	23.400	2.00	2.50
OF20-0800	203	8	4.1	0.16	15	212	35	508	77.150	2.50	3.30
OF20-1000	254	10	3.90	0.15	15	212	35	508	110.250	3.00	3.95
OF20-1200	305	12	4.10	0.16	11	157	26	377	101.400	3.30	5.10

**** In Yellow Version OROFLEX 20 HD Reinforced - To Order ****



- ◆ Contractor Air Hose
- ◆ High Pressure Pump Discharge
- ◆ Drilling Machine Compressor Hose
- ◆ Heavy Duty Dredge Discharge
- ◆ All Oroflex-10 Applications Requiring A Heavier, Higher Pressure Hose
- ◆ Bulk Powder Discharge