



## OROFLEX 30 SL

High Pressure Layflat Hose Specially Designed As A Drag Hose In Sludge And Slurry Applications.

**OROFLEX 30 SL** Is Made From A Tough Polyurethane Compound And Is Designed To Work In Tough Abrasive Environment.

**Color** : Green Or blue

Part Number	Diameter		Wall Thickness	Working Pressure	Burst Pressure	Tensile Strength	Bending Radius	Hose Weight
	mm	inch	mm	bar	bar	kg	mm	kg/m
OF30-0400	102	4	3.5	17	40	13.100	1.750	1.30
OF30-0450	115	4-1/2	3.5	14	35	16.000	1.800	1.50
OF30-0500	127	5	3.7	12	32	18.000	1.900	1.70
OF30-0550	140	5-1/2	3.7	10	28	20.000	1.950	1.90
OF30-0600	152	6	3.8	10	28	25.000	2.000	2.10

\* Total Theoretical Tensile Strength. End Pull At Working Conditions Should Not Pass 1/3 Of This Value.

\* To Order



- ◆ Used As A Drag Hose For Slurry/Manure Injection And Spreading
- ◆ Irrigation Feeding Line
- ◆ Traveler Irrigators
- ◆ Potable Water Transfer (Materials Approved To NSF61 And KTW)  
(Exceeds WRAS Standards.)
- ◆ Compatible With Oils And Fuel