



OSD250 OIL SUCTION/DISCHARGE HOSE 250 PSI

Heavy Duty Suction And Delivery Hose, Excellent For Use As A Tank Truck Or Tank Wagon Hose. It Withstands The Full Vacuum. Its Anti-Static Cover Conforms Fully To PTB Specifications. Used For A Wide Range Of Petroleum Products Up To 50% Aromatic Content.

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F)
- Tube** : Black, Smooth, Nitrile Compound
- Reinforcement** : High Strength Synthetic Cord Plus Helix Wire And Anti-Static Copper Wire
- Cover** : Black, Smooth (Wrapped Finish) High Grade Chloroprene Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion And Oil.
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Orange Transfer Tape With Negative Text
'SUNFLEX OSD 250 OIL SUCTION/DELIVERY HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
OSD250-0200	51	2	65	2-9/16	17	250	51	750	330	1.81	1.24
OSD250-0250	63	2-1/2	80	3-3/16	17	250	51	750	400	2.78	1.87
OSD250-0300	76	3	93	3-21/32	17	250	51	750	500	2.93	2.01
OSD250-0400	102	4	120	4-47/64	17	250	51	750	730	4.95	3.36
OSD250-0500	127	5	149	5-7/8	17	250	51	750	1010	6.60	4.43
OSD250-0600	152	6	174	6-55/64	17	250	51	750	900	7.80	5.24
OSD250-0800	203	8	227	8-15/16	17	250	51	750	1625	15.96	10.72
OSD250-1000	254	10	288	11-11/32	17	250	51	750	2035	22.28	14.97
OSD250-1200	305	12	343	13-1/2	17	250	51	750	2600	30.06	20.18