



SSD250

SUNFLEX SLURRY SUCTION AND DISCHARGE HOSE 250 PSI

Applications: For suction and delivery of abrasive slurry materials

Temperature range: -40°C (-40°F) to +85°C (+185°F)

Construction:-

Tube: 5 - 9 mm - Natural Rubber - super abrasion resistant (S.A.R.)
(Depend on the sizes)

Reinforcement: 6 ply, high tensile synthetic incorporating a wire helix

Cover: 2mm Black, Natural Rubber - Super abrasion resistant (S.A.R.) - Brown Stripe

Branding : Black cover with embossed brown stripe tape

'SUNFLEX SSD250 SUCTION/DELIVERY HOSE WPSI 250'
ISO 1307

PART NO	ID x OD	ID	INNER TUBE (THICKNESS)	WORKING PRESSURE		BENDING RADIUS (MM)	WEIGHT (KG/M) <i>(Exculde Fittings)</i>
	(MM)	(INCH)		BAR	PSI		
SSD250-0800	203X235	8"	5	17BAR	250PSI	2000	16
SSD250-1000	254X289	10"	5			2500	22
SSD250-1200	305X349	12"	6			3660	33
SSD250-1400	356X399	14"	6			4272	38
SSD250-1600	406X459	16"	9			6426	54