



## X Series SAE 4SH / EN856

**Application :** Construction/Agriculture Machine, Industrial Equipment, Machine Tool & Various Hydraulic System

**Operating Temperature :** -40°C to +120°C (-40F to +212F)

**Reinforcement :** Steel Wire

**Inner Cover :** Oil Resistant Synthetic Rubber

**Outer Cover :** Oil & Weather Resistant Synthetic Rubber

**Recommended Fluids :** Mineral Hydraulic Oil

**Max. Impulse Test Pressure :** 133% Of Max. Working Pressure

**Branding :** White Positive Text

**SUNFLEX X SERIES DIN EN 856/4SH MSHA IC-263/2 - FLAME RESISTANT**

Part Number	Hose Size			Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
	I.D.		O.D.	psi	bar	psi	bar	inch	mm	g/m
	inch	mm	mm							
4SHB-12-SF-TX	3/4	19.2	31.8	6,100	420	24,000	1680	9.06	230	1,450
4SHB-16-SF-TX	1	25.4	38.8	5,500	380	22,000	1520	9.45	240	2,010
4SHB-20-SF-TX	1-1/4	31.8	45.7	4,500	350	18,000	1400	9.84	250	2,565
4SHB-24-SF-TX	1-1/2	38.1	63.0	4,200	290	16,800	1160	12.20	310	3,130
4SHB-32-SF-TX	2	50.8	67.8	3,620	250	14,480	1000	17.72	450	4,975

### FEATURES

- Flexibility Performance
- Good Anti-aging Performance
- Long Impulse Pressure Life
- Economic And Environmental
- High Pressure Large Diameter Series
- No Need Skiving