



## X Series SAE 4SP / EN856

**Application :** Construction/Agriculture Machine, Industrial Equipment, Machine Tool & Various Hydraulic System

**Operating Temperature :** -40°C to +120°C (-40F to +212F)

**Reinforcement :** Steel Wire

**Inner Cover :** Oil Resistant Synthetic Rubber

**Outer Cover :** Oil & Weather Resistant Synthetic Rubber

**Recommended Fluids :** Mineral Hydraulic Oil

**Max. Impulse Test Pressure :** 133% Of Max. Working Pressure

**Branding :** White Positive Text

**SUNFLEX X SERIES DIN EN 856/4SP MSHA IC-263/2 - FLAME RESISTANT**

Part Number	Hose Size			Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
	I.D.		O.D.	psi	bar	psi	bar	inch	mm	g/m
	inch	mm	mm							
R9R-06-SF-TX	3/8	09.5	21.3	6,000	445	24,000	1780	5.12	130	645
R9R-08-SF-TX	1/2	12.9	24.4	6,000	415	24,000	1660	5.51	140	730
R9R-10-SF-TX	5/8	16.0	28.0	5,500	380	22,000	1520	6.30	160	1,025
R9R-12-SF-TX	3/4	19.2	31.8	5,500	380	22,000	1520	7.87	200	1,450
R9R-16-SF-TX	1	25.4	39.4	4,650	325	18,600	1300	9.06	230	1,945

### FEATURES

- Flexibility Performance
- Good Anti-aging Performance
- Long Impulse Pressure Life
- Economic And Environmental
- High Pressure Large Diameter Series
- No Need Skiving