



## X6KP - 4/6 Steel Wire Spiral Hose

### Construction

**Core:** Special synthetic rubber tube resistant to mineral. Vegetable and glycol based hydraulic oil

**Reinforcement:** 4 or 6 high tensile strength steel wire reinforced

**Cover:** Super high abrasion and weather resistance special synthetic rubber cover

**Temperature Range:** -40°C to +120°C

**Application:** For hydraulic systems with high peak pressure and arduous operating condition such as high pressure hydraulic circuits (for example on booms) on mobile construction equipment, mining equipment, agriculture machines.

**Branding:** Orange transfer tap with negative text

'SUNFLEX X6KP EXCEEDS ISO 18752-CC/SAE 100 R15 PERFORMANCE

### Technical Details

SUNFLEX	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	4 or 6 Spiral
		(In.)	(mm)	(In.)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In.)		
<b>X6KP-06-SF-S</b>	6	3/8	9.5	0.82	20.9	6,090	420	24,360	1,680	65	2.6	0.70	4
<b>X6KP-08-SF-S</b>	8	1/2	12.7	0.96	24.4	6,090	420	24,360	1,680	90	3.6	0.92	4
<b>X6KP-10-SF-S</b>	10	5/8	15.9	1.11	28.1	6,090	420	24,360	1,680	100	4.0	1.13	4
<b>X6KP-12-SF-S</b>	12	3/4	19	1.21	30.7	6,090	420	24,360	1,680	150	6.0	1.246	4
<b>X6KP-16-SF-S</b>	16	1	25.4	1.49	37.9	6,090	420	24,360	1,680	210	8.4	1.828	4
<b>X6KP-20-SF-S</b>	20	1.1/4	31.8	1.95	49.6	6,090	420	24,360	1,680	260	10.4	3.166	6
<b>X6KP-24-SF-S</b>	24	1.1/2	38.1	2.24	56.9	6,090	420	24,360	1,680	310	12.4	4.396	6
<b>X6KP-32-SF-S</b>	32	2	50.8	2.83	72.0	6,090	420	24,360	1,680	350	14.0	6.252	6