



SUNFLEX 352 VERY HIGH PRESSURE HOSE WP 10000PSI

- APPLICATION** : Very High Pressure Hydraulic Lines 520 To 700 Bar. Compact, High Pressure, Light Weight, High Abrasion Resistance And Low Change In Length. For Use With Petroleum, Synthetic Or Water Based Fluids In Hydraulic Systems. Mainly Used For Rescue, Safety Equipment, Bolt Tensioning Tools And Jacking & Re-Railing Equipments. Also, Suitable For Earthmoving And Material Handling Equipments.
- CORE** : Thermoplastic Elastomer
- REINFORCEMENT** : Double Braids Of Aramid Fibre With Single Steel Wire Braid
- COVER** : Orange Color Polyurethane. Available Twin And Multi Lines With Different Hose Combination And Size
- TEMPERATURE RANGE** : -40°C to +100°C. Temperature Not Exceed +70°C For Air And Water Based Fluids

Part Number	Nominal Inside Diameter		Nominal Outside Diameter		Working Pressure		Bursting Pressure		Minimum Bending Radius		Hose Weight
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/mt
352-04-SF	1/4	6.4	0.540	13.7	10,000	700	40,000	2800	2.8	70	242
352-06-SF	3/8	9.6	0.740	18.8	10,000	700	40,000	2800	4.0	100	387
352-08-SF	1/2	12.7	0.875	22.2	10,000	700	30,000	2080	7.0	180	514