



SUNFLEX 350 VERY HIGH PRESSURE HOSE WP 10000PSI

- APPLICATION** : Very High Pressure Hydraulic Lines 300 To 700 Bar. Compact, High Pressure, Light Weight, High Abrasion Resistance And Low Change In Length. For Use With Petroleum, Synthetic Or Water Based Fluids In Hydraulic Systems. Mainly Used For Rescue, Safety Equipment, Bolt Tensioning Tools And Jacking & Re-Railing Equipments. Also, Suitable For Earthmoving And Material Handling Equipments.
- CORE** : Thermoplastic Elastomer
- REINFORCEMENT** : Double Braids Of Aramid Fibre With Single Steel Wire Braid
- COVER** : Black Color Polyurethane. Available Twin And Multi Lines With Different Hose Combination And Size. **Also special colours available on request.**
- TEMPERATURE RANGE** : -40°C to +100°C. Temperature Not Exceed +70°C For Air And Water Based Fluids

Part Number	Nominal Inside Diameter		Nominal Outside Diameter		Working Pressure		Bursting Pressure		Minimum Bending Radius		Hose Weight
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/mt
350-04-SF	1/4	6.4	0.555	14.1	10,000	700	25,000	1750	4.0	100	356
350-06-SF	3/8	9.5	0.690	17.5	10,000	700	21,750	1500	6.0	150	513
350-08-SF	1/2	12.7	0.830	21.1	7,250	500	18,125	1250	8.0	200	678